

UTILITY PATENT APPLICATION TRANSMITTAL

Attorney Docket No.

1341.1063/JDH

First Named Inventor or Application Identifier:

Taichi UJIGAWA, et al.

Express Mail Label No.

(Only for new nonprovisional applications under 37 CFR 1.53(b))

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO:

**Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231**

1. ☒ Fee Transmittal Form
2. ☒ Specification, Claims & Abstract [Total Pages: 75]
3. ☒ Drawing(s) (35 USC 113) [Total Sheets: 25]
4. ☒ Oath or Declaration [Total Pages: 4]
 - a. ☒ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 CFR 1.63(d)) (for continuation/divisional with Box 17 completed)
 - i. ☐ **DELETION OF INVENTOR(S)**
Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation by Reference (usable if Box 4b is checked)
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.
6. ☐ Microfiche Computer Program (Appendix)
7. ☐ Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
 - b. ☐ Computer Readable Copy
 - c. ☐ Paper Copy (identical to computer copy)
 - d. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. ☒ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement (when there is an assignee) [] Power of Attorney
10. ☐ English Translation Document (if applicable)
11. ☒ Information Disclosure Statement (IDS)/PTO-1449[X] Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503) (Should be specifically itemized)
14. ☐ Small Entity Statement(s) [] Statement filed in prior application, status still proper and desired.
15. ☒ Certified Copy of Priority Document(s) (if foreign priority is claimed)
16. ☐ Other:

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:[] Continuation [] Divisional [] Continuation-in-part (CIP) of prior application No: 1**18. CORRESPONDENCE ADDRESS**

21171

PATENT TRADEMARK OFFICE

Staas & Halsey

NEW APPLICATION FEE TRANSMITTAL

Attorney Docket No.	1341.1063/JDH
Application Number	To Be Assigned
Filing Date	October 25, 2000
First Named Inventor	Taichi UJIGAWA, et al.

AMOUNT ENCLOSED	\$750.00
-----------------	----------

FEE CALCULATION (fees effective 10/01/00)

CLAIMS	(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS
	TOTAL CLAIMS	8	- 20 =	0	X \$ 18.00 = \$ 0.00
	INDEPENDENT CLAIMS	2	- 3 =	0	X \$ 80.00 = 0.00
	MULTIPLE DEPENDENT CLAIMS (any number, if applicable)			+ \$270.00 =	0.00
	BASIC FILING FEE				710.00
	Total of above Calculations =				\$ 710.00
	Surcharge for late filing fee, Statement or Power of Attorney (\$130.00)				
	Reduction by 50% for filing by small entity (37 CFR 1.9, 1.27 & 1.28).				-
	TOTAL FILING FEE =				\$ 710.00
	Surcharge for filing non-English language application (\$130.00; 37 CFR 1.52(d))				+
	Recordation of Assignment (\$40.00; 37 CFR 1.21(h)(1))				40.00
	TOTAL FEES DUE =				\$ 750.00

METHOD OF PAYMENT

- ☒ Check enclosed as payment.
- ☐ Charge "TOTAL FEES DUE" to the Deposit Account No., below.
- ☐ No payment is enclosed and no charges to the Deposit Account are authorized at this time.

GENERAL AUTHORIZATION

- ☒ If the above-noted "AMOUNT ENCLOSED" is not correct, the Commissioner is hereby authorized to credit any overpayment or charge any additional fees necessary to:

Deposit Account No.


19-3935

Deposit Account Name

STAAS & HALSEY LLP

- ☒ The Commissioner is also authorized to credit any overpayments or charge any additional fees required under 37 CFR 1.16 (filing fees) or 37 CFR 1.17 (processing fees) during the prosecution of this application, including any related application(s) claiming benefit hereof pursuant to 35 USC § 120 (e.g., continuations/divisionals/CIPs under 37 CFR 1.53(b) and/or continuations/divisionals/CPAs under 37 CFR 1.53(d)) to maintain pendency hereof or of any such related application.

SUBMITTED BY: STAAS & HALSEY LLP

Typed Name	James D. Halsey, Jr.	Reg. No.	22,729
Signature		Date	October 25, 2000

INFORMATION COLLECTION AND DISTRIBUTION SYSTEM

FIELD OF THE INVENTION

The present invention relates to an information
5 collection and distribution system for collecting and
distributing information between computers which are
connected to each other through a network.

BACKGROUND OF THE INVENTION

10 In recent years, with rapid spread of an advanced
communication infrastructure represented by the Internet,
collection and distribution of information between computers
(e.g., between a server and a client) are generally performed
according to a communication protocol such as the HTTP
15 (Hypertext Transfer Protocol), the IIOP (Internet Inter ORB
Protocol) or the FTP (File Transfer Protocol). However,
recently, the following problems have arisen.

(1) In information collection and distribution through the
Internet, illegal acts such as falsification, wiretapping, and
20 pretending may be performed. For this reason, an operation
load on a system manager for ensuring security tends to
increase.

(2) With an increase in the number of accesses with an
increase of the number of users, or an increase in the quantity
25 of information (image data, audio data, computer program, and

the like) to be collected and distributed, a load on a network increases.

(3) With an increase in the number of client device, a load on a server for controlling collection and distribution of information increases.

Accordingly, means and method for effectively solving the above-mentioned problems is in demand.

Fig. 22 is a block diagram showing an example of configuration of a conventional information collection and distribution system. In this diagram, a client/server type information collection and distribution system which is structured through a network having a LAN (Local Area Network) - WAN (Wide Area Network) - LAN form is shown. A main office network system 10 is an in-house system, and is constituted by a main office server 11, a LAN 13, and a fire wall 14.

The main office server 11 comprises a function of distributing information (e.g., an application program 12) to an employee 0 client 33₀, to an employee n client 33_n (to be described later) and a function of collecting information from the employee 0 client 33₀ and the employee n client 33_n. The main office server 11 is connected to the LAN 13. The fire wall 14 is used to prevent illegal access to the main office network system 10 from an external system, and is designed to pass only information or a protocol to which a security is given. The LAN 13 is an in-house network installed in the main office,

and is connected to the Internet 20 through the fire wall 14.

A branch office network system 30 is an in-house system structured in a branch office, and is constituted by a fire wall 31, a LAN 32, and an employee 0 client 33, to an employee n client 33_n. The fire wall 31 is used to prevent illegal access to the branch office network system 30. The LAN 32 is an in-house network installed in the branch office, and is connected to the Internet 20 through the fire wall 31. The employee 0 client 33, to the employee n client 33_n are computers which are arranged for an employee 0 to an employee n (not shown) in the branch office, respectively, and are connected to the LAN 32.

Operation of the information collection and distribution system shown in Fig. 22 will be described below with reference to a sequence chart shown in Fig. 23. In step F1 in Fig. 23, the main office server 11 transmits an application program 12 as a communication block to the employee 0 client 33, through the LAN 13, the fire wall 14, the Internet 20, the fire wall 31, and the LAN 32 (to be referred to as a network hereinafter) to distribute the application program 12 as information to the employee 0 client 33, to the employee n client 33_n by a circulation system.

When the communication block (application program 12) is received, in step F2, the employee 0 client 33, stores a copy of the application program 12 in a storage device (not

shown), and then notifies the main office server 11 of a progress status of distribution through the network. Here, the status is that the communication block is received, i.e., that the communication block is circulated to the employee 1
5 client 33₁ which is a circulation destination.

In step F3, the employee 0 client 33₀ transmits (circulates) a communication block to the employee 1 client 33₁ which is the next circulation destination through the LAN 32. When the communication block is received, in step F4, the
10 employee 1 client 33₁ stores a copy of the application program 12 in the storage device, and then notifies the main office server 11 of a progress status of distribution through the network.

In step F5, the employee 1 client 33₁ transmits
15 (circulates) the communication block to the employee 2 client 33₂ which is a circulation destination through the LAN 32. Thereafter, the clients subsequent to the employee 2 client 33₂ notify the main office server 11 of statuses, and sequentially transmit communication blocks to clients which
20 are next circulation destinations.

When a communication block is transmitted to the employee n client 33_n which is the final circulation destination, the employee n client 33_n, the employee n client 33_n stores a copy of the application program 12 in the storage
25 device, and then notifies the main office server 11 of a

progress status of distribution through the network.

In this manner, in the conventional information collection and distribution system, a communication program is transmitted to the employee 0 client 33₀ which represents
5 the employee 0 client 33₀ and the employee n client 33_n, and communication blocks are sequentially circulated to the employee 0 client 33₀ → the employee 1 client 33₁ → ... → the employee n client 33_n in the branch office network system 30, so that information distribution is realized.

10 On the other hand, in the conventional information collection and distribution system, status notifications are performed from the employee 0 client 33₀ to the employee n client 33_n, respectively, so that collection of pieces of information is realized on the main office server 11 side.

15 Fig. 24 is a block diagram showing another example of the configuration of a conventional information collection and distribution system. The same reference numerals as in Fig. 22 denote the same parts in Fig. 24. In Fig. 24, a dedicated server 40 for controlling collection and distribution on the
20 branch office network system 30 side is newly connected to the LAN 32.

Operation of the information collection and distribution shown in Fig. 24 will be described below with reference to the sequence diagram shown in Fig. 25. In step
25 G1 shown in Fig. 25, the main office server 11 transmits the

application program 12 to the dedicated server 40 through the Internet 20 to distribute the application program 12 as information to the employee 0 client 33₀, to the employee n client 33_n by a circulation system.

5 When the application program 12 is received, in step G2, the dedicated server 40 transmits (circulates) the application program 12 to the employee 0 client 33₀, which is the first circulation destination through the LAN 32. When the application program 12 is received, in step G3, the employee
10 0 client 33₀ stores a copy of the application program 12 in the storage device, and then notifies the dedicated server 40 of a progress status of distribution through the LAN 32. Here, the status is that the application program 12 is distributed.

 In step G4, the dedicated server 40 transmits the
15 application program 12 to the employee 1 client 33₁, which is the next circulation destination through the LAN 32. When the application program 12 is received, in step G5, the employee 1 client 33₁ stores a copy of the application program 12 in the storage device, and then notifies the dedicated server 40
20 of a progress status of distribution through the LAN 32. Thereafter, transmission of the application program 12 from the dedicated server 40 to the client which is a circulation destination and status notification from the client to the dedicated server 40 are sequentially performed.

25 When the application program 12 is transmitted to the

employee n client 33_n which is the final circulation destination in step G6, in step G7, the employee n client 33_n stores a copy of the application program 12 in the storage device, and then notifies the dedicated server 40 of a progress
5 status of distribution through the LAN 32.

In this manner, when distribution (circulation) to the employee 0 client 33₀ to the employee n client 33_n is completed, in step G8, the dedicated server 40 notifies the main office server 11 of an entire status obtained by collecting status
10 notifications which are respectively received from the employee 0 client 33₀ to the employee n client 33_n through the network.

Techniques related to the information collection and distribution by the circulation system are disclosed in
15 Japanese Unexamined Patent Publication No. 9-8801, Japanese Examined Patent Publication No. 2740105, Japanese Unexamined Patent Publication No. 6-216934 and Japanese Unexamined Patent Publication No. 11-25185, respectively.

However, in the information collection and distribution
20 system shown in Fig. 22, the status notifications are respectively performed from the employee 0 client 33₀ to the employee n client 33_n to the main office server 11. For this reason, an amount of traffic on the network increases in proportion to the number of clients. Accordingly, the network
25 and the main office server 11 disadvantageously receive a heavy

load.

In addition, the information collection and distribution system shown in Fig. 22 is designed such that status notifications are respectively performed from the employee 0 client 33₀ to the employee n client 33_n. For this reason, it is not preferable that traffic passes through the fire wall 31 every status notification. Therefore, a load on a system manager for securing a security disadvantageously increases.

On the other hand, in the information collection and distribution system shown in Fig. 24, the dedicated server 40 is arranged to perform status notifications to the main office server 11 at once. For this reason, load on the Internet 20 and the LAN 13 are reduced, and the information collection and distribution system is more secured as compared to the information collection and distribution system shown in Fig. 22.

However, in the information collection and distribution system shown in Fig. 24, status notifications are still performed from the employee 0 client 33₀ to the employee n client 33_n to the dedicated server 40, respectively. For this reason, a heavy load disadvantageously acts on the LAN 32. In the information collection and distribution system shown in Fig. 24, the dedicated server 40 must be arranged independently of the employee 0 client 33₀ to the employee n client 33_n, so that

the costs disadvantageously increase.

In addition, in the information collection and distribution systems shown in Fig. 22 and Fig. 24, the circulation system is employed between the employee 0 client 33, to the employee n client 33_n. For this reason, a long period of time is disadvantageously required to end all the collection and distribution.

SUMMARY OF THE INVENTION

It is an object of this invention to provide an information collection and distribution system which can reduce load on the network cheaply, which has high security, and which can shorten a period of time required for collection and distribution.

In the information collection and distribution system according to the present invention, the server transmits communication blocks including at least addresses and pieces of distribution information of the plurality of clients to one client of the plurality of clients through the network. One client (the first client) obtains the pieces of distribution information from the communication blocks, and circulates the communication blocks in which distribution results are set to the next client on the basis of the addresses (thus, the information is distributed to clients one after the other). A final client (a client that has received the information last)

transmits the communication block to the first client. The first client relays the communication block transmitted from the final client of the circulation destination to the server.

Thus, when a communication block is transmitted from the
5 server to the first client, the first client obtains a piece of distribution information from the communication block, sets the distribution result in the communication block, and circulates the communication block to a client of the next circulation destination. Thereafter, communication blocks
10 are sequentially circulated from clients to clients. In this manner, the respective clients obtain pieces of distribution information from communication blocks, and set distribution results in the communication blocks. A communication block from the final client of the circulation destination is relayed
15 to the server through one client.

Thus, the first client performs the relay of information. When circulation of all communication blocks is completed, a communication block in which a distribution result is set is relayed to a server through the first client. For this reason,
20 unlike the conventional technique, a dedicated server need not be arranged, and only a communication block may transmitted from an in-house network to an external network once. Therefore, a network load can be reduced cheaply and a high security can be maintained.

25 Other objects and features of this invention will become

apparent from the following description with reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

5 Fig. 1 is a block diagram showing the configuration of a first embodiment according to the present invention.

 Fig. 2 is a diagram showing the data structure of a basic communication block 700 used in the first embodiment.

 Fig. 3 is a diagram showing the data structure of a
10 distribution communication block 800 used in the first embodiment.

 Fig. 4 is a diagram showing the data structure of a collection communication block 900 used in the first embodiment.

15 Fig. 5 is a flow chart for explaining an operation of a communication block forming unit 150 shown in Fig. 1.

 Fig. 6 is a flow chart for explaining an operation of a collection and distribution controller 130 shown in Fig. 1.

 Fig. 7 is a flow chart for explaining an operation of
20 a result management unit 190 shown in Fig. 1.

 Fig. 8 is a flow chart for explaining operations of collection and distribution controllers 420 and 620 shown in Fig. 1.

 Fig. 9 is a flow chart for explaining operations of
25 circulation controllers 450 and 650 shown in Fig. 1.

Fig. 10 is a sequence diagram for explaining a distribution operation in Operational Example 1 of the first embodiment.

Fig. 11 is a sequence diagram for explaining a
5 distribution operation in Operational Example 1 of the first embodiment.

Fig. 12 is a sequence diagram for explaining a retry distribution operation in Operational Example 1 of the first embodiment.

10 Fig. 13 is a flow chart for explaining an operation of a circulation controller in Operational Example 2 of the first embodiment.

Fig. 14 is a sequence diagram for explaining a
15 distribution operation in Operational Example 2 of the first embodiment.

Fig. 15 is a block diagram for explaining Operational Example 3 of the first embodiment.

Fig. 16 is a flow chart for explaining an operation of a circulation controller 450 shown in Fig. 1.

20 Fig. 17 is a flow chart for explaining an operation of a partition processor 490 shown in Fig. 1.

Fig. 18A to Fig. 18D are diagrams showing the data structures of partitioned distribution communication blocks 800₁ to 800_x used in Operational Example 3 of the first
25 embodiment.

Fig. 19 is a sequence diagram for explaining a partitioned distribution operation in Operational Example 3 of the first embodiment.

Fig. 20 is a block diagram showing the configuration of
5 a second embodiment according to the present invention.

Fig. 21 is a diagram showing state transitions of a distribution communication block 1300 used in the second embodiment.

Fig. 22 is a block diagram showing an example of
10 configuration of a conventional information collection and distribution system.

Fig. 23 is a sequence diagram for explaining an operation of the information collection and distribution system shown in Fig. 22.

Fig. 24 is a block diagram showing an another example
15 of configuration of a conventional information collection and distribution system.

Fig. 25 is a sequence diagram for explaining an operation of the information collection and distribution system shown
20 in Fig. 24.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Two preferred embodiments of an information collection and distribution system according to the present invention
25 will be described below with reference to the accompanying

drawings.

Fig. 1 is a block diagram showing the configuration of a first embodiment according to the present invention. In Fig. 1, a client/server type information collection and distribution system constructed through the Internet 200 is shown. A server 100 comprises a function of distributing pieces of information to client groups 300_1 to 300_n and a function of collecting pieces of information from the client groups 300_1 to 300_n . As the pieces of information which are mentioned here, various data, various files, computer programs, and the like are used. The server 100 is connected to the Internet 200 through the fire wall to prevent illegal access from an external system.

The client group 300_1 is constituted by $n + 1$ clients, i.e., a relay client 400 and clients 600_1 to 600_n . Unique addresses are given to the relay client 400 and the clients 600_1 to 600_n , respectively. Each of the client groups 300_2 to 300_n is also constituted by a plurality of clients (including a relay client) like the client group 300_1 .

In the server 100, an operation unit 110 is a keyboard, a mouse, or the like for inputting information required to operate collection and distribution and to output the results of collection and distribution. A display unit 120 is an LCD (Liquid Crystal Display) or a CRT (Cathode-Ray Tube) for displaying various pieces of information used in collection

and distribution. A collection and distribution controller 130 performs collection and distribution control. An operation of the collection and distribution controller 130 will be described below with reference to a flow chart.

5 A data storage unit 140 stores information to be distributed, collected information, and a communication block (to be described later). A communication block forming unit 150 forms a communication block used in collection and distribution to store the communication block in the data
10 storage unit 140. As communication blocks mentioned here, a basic communication block 700 (see Fig. 2), a distribution communication block 800 (see Fig. 3), and a collection communication block 900 (see Fig. 4) are used. As the descriptive forms of the basic communication block 700, the
15 distribution communication block 800, and the collection communication block 900, a binary form, a text form, an XML (eXtensible Markup Language) form which rapidly spreads in recent years, and the like are used.

The basic communication block 700 shown in Fig. 2 is
20 constituted by a start header 710, a collection and distribution ID 720, a circulation information region header 730, a circulation information region 740, a distribution information header 750, a distribution information region 760, a collection information header 770, and a collection
25 information region 780 to perform collection and distribution

in units of client groups each constituted by m clients.

The start header 710 is a header indicating a start position (leading position) of the basic communication block 700. The collection and distribution ID 720 is an identifier
5 for uniquely identifying a communication job (collection or distribution). Therefore, the collection and distribution ID 720 is given to each communication job. The circulation information region header 730 is a header indicating a start position of the circulation information region 740. In the
10 circulation information region 740, pieces of information related to circulation such as the client name of a circulation destination, an address, and the like are set.

More specifically, in the circulation information region 740, $(n + 1)$ pairs of pieces of information, i.e., a
15 circulation destination information header 741_0 and a circulation destination information 742_0 (one pair), a circulation destination header 741_1 and a circulation destination information 742_1 (one pair), ..., and a circulation destination information header 741_n and a circulation
20 destination information 742_n (one pair) are set. These $(n + 1)$ pairs of pieces of information correspond to the $(n + 1)$ clients, e.g., the relay client 400 (upper level client) and the clients 600_1 to 600_n (lower level clients) in the client group 300_i shown in Fig. 1, respectively.

25 The circulation destination information headers 741_i to

741_n are headers indicating the start positions of the pieces of circulation destination information 742₀ to 742_n, respectively. The pieces of circulation destination information 742₀ to 742_n are constituted by information related to a destination (client) of circulation and information for management. More specifically, the circulation destination information 742₀ is constituted by a client name 743₀, an address 744₀, a collection and distribution management information region header 745₀, a collection and distribution management flag 746₀, a result management information 747₀, and a result management information region 748₀. The client name 743₀ is the name of a circulation destination (in this case, the relay client 400). The address 744₀ is the address of the circulation destination (in this case, the relay client 400).

15 The collection and distribution management information region header 745₀ is a flag indicating the start position of the collection and distribution management flag 746₀. The collection and distribution management flag 746₀ is a flag for managing a collection and distribution status, i.e.,

20 "collected", "uncollected", "distributed", or
 "undistributed". In this case, when the collection and distribution management flag 746₀ is "collected" (or "distributed"), it means that information related to the relay client 400 is collected (distributed). On the other hand, when

25 the collection and distribution management flag 746₀ is

"uncollected" (or "undistributed"), it means that information related to the relay client 400 is not collected (distributed).

The result management information 747₀ is a flag indicating the start position of the result management information region 748₀. The result management information region 748₀ indicates the result of collection and distribution, i.e., "normal", "abnormal", "undefined". In this case, when the result management information region 748₀ is "normal", it means that the collection and distribution related to the relay client 400 is normally performed. When the result management information region 748₀ is "abnormal", it means that the collection and distribution related to the relay client 400 cannot be performed due to defect or the like. When the result management information region 748₀ is "undefined", it means that the collection and distribution related to the relay client 400 have not been performed.

The circulation destination information 742₁ has the same data structure as that of the circulation destination information 742₀ described above, and is constituted by a client name 743₁, an address 744₁, a collection and distribution management information region header 745₁, a collection and distribution management flag 746₁, a result management information 747₁, and a result management information region 748₁. The client name 743₁ is the name of a circulation destination (in this case, the client 600₁). The address 744₁

is the address of the circulation destination (in this case, the client 600₁).

The collection and distribution management information region header 745₁ is a flag indicating the start position of the collection and distribution management flag 746₁. The collection and distribution management flag 746₁ is a flag for managing a collection and distribution status, i.e., "collected", "uncollected", "distributed", or "undistributed". In this case, when the collection and distribution management flag 746₁ is "collected" (or "distributed"), it means that information related to the client 600₁ is collected (distributed). On the other hand, when the collection and distribution management flag 746₁ is "uncollected" (or "undistributed"), it means that information related to the client 600₁ is not collected (distributed).

The result management information 747₁ is a flag indicating the start position of the result management information region 748₁. The result management information region 748₁ indicates the result of collection and distribution, i.e., "normal", "abnormal", "undefined". In this case, when the result management information region 748₁ is "normal", it means that the collection and distribution related to the client 600₁ are normally performed. When the result management information region 748₁ is "abnormal", it means that the collection and distribution related to the client 600₁ cannot

be performed due to defect or the like.

When the result management information region 748_1 is "undefined", it means that collection and distribution related to the client 600_1 have not been performed. Subsequently, by the same manner as described above, the circulation destination information 742_n has the same data structure as those of the circulation destination information 742_0 and the circulation destination information 742_1 , and is information corresponding to the client 600_n .

The distribution information header 750 is a header indicating the start position of the distribution information region 760. In the distribution information region 760, information to be distributed (computer program or the like) is set. The collection information header 770 is a header indicating the start position of the collection information region 780. In the collection information region 780, information related to collection is set. More specifically, in the collection information region 780, $(n + 1)$ sets of pieces of information, i.e., a client name 781_0 , an address 782_0 , collection information 783_0 (one set), a client name 781_1 , an address 782_1 , collection information 783_1 (one set), ..., and a client name 781_n , an address 782_n , collection information 783_n (one set).

These $(n + 1)$ sets of pieces of information correspond to the $(n + 1)$ clients, e.g., the relay client 400 and the

clients 600_1 to 600_n in the client group 300_1 shown in Fig. 1, respectively.

The client name 781_0 is the name of a client (in this case, the relay client 400) to which the collection information 783₀ is to be provided. The address 782_0 is an address given to the relay client 400. The collection information 783₀ is information collected in the server 100, and is information provided from the relay client 400.

The client name 781_1 is the name of a client (in this case, the client 600_1) to which the collection information 783₁ is to be provided. The address 782_1 is an address given to the client 600_1 . The collection information 783₁ is information collected in the server 100, and is information provided from the client 600_1 .

Subsequently, similarly, the client name 781_n is the name of a client (in this case, the client 600_n) to which the collection information 783_n is to be provided. The address 782_n is an address given to the client 600_n . The collection information 783_n is information collected in the server 100, and is information provided from the client 600_n .

The distribution communication block 800 shown in Fig. 3 is obtained by extracting information required for distribution from the basic communication block 700 shown in Fig. 2, and is constituted by pieces of information except for the collection information header 770 and the collection

information region 780 (see Fig. 2). The same reference numerals as in Fig. 2 denote the same parts in Fig. 3. The distribution communication block 800 is used when information is distributed to the client group 300₁ shown in Fig. 1. When
5 pieces of information are distributed to the client groups 300₂ to 300_m, a plurality of distribution communication blocks each having the same data structure as that of the distribution communication block 800 are also formed.

The collection communication block 900 shown in Fig. 4
10 is obtained by extracting information required for collection from the basic communication block 700 shown in Fig. 2, and is constituted by pieces of information except for the distribution information header 750 and the distribution information region 760 (see Fig. 2). The same reference
15 numerals as in Fig. 2 denote the same parts in Fig. 4. The collection communication block 900 is used when information is collected from the client group 300₁ shown in Fig. 1. When pieces of information are collected from the client groups 300₂ to 300_m, a plurality of collection communication blocks each
20 having the same data structure as that of the collection communication block 900 are also formed.

Referring again to Fig. 1, a data processor 160 of the server 100 executes data processing to the distribution communication block 800 and the basic communication block 700.
25 A transmission processor 170 transmits the distribution

communication block 800 or the collection communication block 900 to, e.g., the relay client 400 of the client group 300₁ through the Internet 200. A reception processor 180 receives the distribution communication block 800 or the collection communication block 900 through the internet 200. A result management unit 190 manages the results of collection and distribution.

In the client group 300₁, the relay client 400 and the clients 600₁ to 600_n are (n + 1) computers, and circulate the distribution communication block 800 or the collection communication block 900 by a circulation system to realize distribution or collection. In this case, the relay client 400 also comprises, in addition to the functions of the clients 600₁ to 600_n, a relaying function which relays the distribution communication block 800 or the collection communication block 900 between the server 100 and the clients 600₁ to 600_n. The relay client 400 and the clients 600₁ to 600_n are connected to each other through a LAN 500. In fact, the LAN 500 is connected to the Internet 200 through the fire wall.

In the relay client 400, a reception processor 410 receives the distribution communication block 800 or the collection communication block 900 from the server 100 through the Internet 200. A collection and distribution controller 420 is to perform collection and distribution control. The details of an operation of the collection and distribution

controller 420 will be described later with reference to a flow chart. A data processor 430 performs data processing to the distribution communication block 800 or the collection communication block 900. A data storage unit 440 stores
5 distribution information or other data distributed from the server 100.

A circulation controller 450 performs circulation control using the distribution communication block 800 or the collection communication block 900. A transmission processor
10 460 transmits the distribution communication block 800 or the collection communication block 900 to the client 600₁ through the LAN 500. A reception processor 470 receives the distribution communication block 800 or the collection communication block 900 through the LAN 500.

15 A transmission processor 480 transmits the distribution communication block 800 or the collection communication block 900 to the server 100 through the Internet 200. A partition processor 490 executes processing when the clients 600₁ to 600_n into a plurality of groups as will be described later in
20 Operational Example 3. The details of an operation of the partition processor 490 will be described later.

In the client 600₁, a reception processor 610 receives the distribution communication block 800 or the collection communication block 900 from the relay client 400 through the
25 LAN 500. A collection and distribution controller 620 is to

perform collection and distribution control. The details of an operation of the collection and distribution controller 620 will be described later with reference to a flow chart. A data processor 630 performs data processing to the distribution communication block 800 or the collection communication block 900. A data storage unit 640 stores distribution information or other data distributed from the server 100.

A circulation controller 650 performs circulation control using the distribution communication block 800 or the collection communication block 900. A transmission processor 660 transmits the distribution communication block 800 or the collection communication block 900 to the client 600₂ through the LAN 500. A reception processor 670 receives the distribution communication block 800 or the collection communication block 900 through the LAN 500.

A transmission processor 680 transmits the distribution communication block 800 or the collection communication block 900 to the relay client 400 through the LAN 500. A partition processor 690 executes processing when the clients 600₁ to 600_n into a plurality of groups as will be described later in Operational Example 3. The details of an operation of the partition processor 690 will be described later.

Operational Example 1 of the first embodiment will be described below with reference to flow charts respectively shown in Fig. 5 to Fig. 9 and sequence diagrams respectively

shown in Fig. 10 to Fig. 12. Fig. 5 is a flow chart for explaining an operation of the communication block forming unit 150 in the server 100 shown in Fig. 1, and Fig. 6 is a flow chart for explaining an operation of the collection and distribution controller 130 in the server 100 shown in Fig. 1.

Fig. 7 is a flow chart for explaining an operation of the result management unit 190 in the server 100 shown in Fig. 1, and Fig. 8 is a flow chart for explaining operations of the collection and distribution controllers 420 and 620 in the relay client 400 and the client 600₁ shown in Fig. 1. Fig. 9 is a flow chart for explaining an operation of the circulation controller 450 or 650 shown in Fig. 1. Fig. 10 is a sequence diagram for explaining a distribution operation in Operational Example 1 of the first embodiment. Fig. 11 is a sequence diagram for explaining a distribution operation in Operational Example 1 of the first embodiment. Fig. 12 is a sequence diagram for explaining a retry distribution operation in Operational Example 1.

First, a distribution operation in Operational Example 1 of the first embodiment will be described below with reference to Fig. 5 to Fig. 10. Subsequently, a case in which distribution information is distributed from the server 100 to the client group 300₁ by a circulation system using the distribution communication block 800 will be described below.

In step SB1 shown in Fig. 6, the collection and distribution controller 130 in the server 100 calls the communication block forming unit 150.

In this manner, in step SA1 shown in Fig. 5, the
5 communication block forming unit 150 determines a processing type (normal collection and distribution processing, retry distribution processing, and cancel processing). As the normal collection and distribution processing, distribution processing using the distribution communication block 800 and
10 collection processing using the collection communication block 900 are known.

In this case, when it is assumed that distribution processing designated by the collection and distribution controller 130, in step SA6, the communication block forming
15 unit 150 forms the distribution communication block 800 shown in Fig. 3 from the basic communication block 700 (see Fig. 2), and then sets a collection and distribution ID 720 for normal collection and distribution is set in the distribution communication block 800. When cancel processing is designated,
20 in step SA8, the communication block forming unit 150 sets a collection and distribution ID 720 for canceling.

In step SA7, the communication block forming unit 150 sets all the pieces of circulation destination information 742, to 742_n shown in Fig. 3. More specifically, as destinations
25 of circulation using the distribution communication block 800,

all the relay client 400 and the clients 600_i to 600_n shown in Fig. 1 are set.

In step SA4, the communication block forming unit 150 determines whether distribution processing is performed by the control of the collection and distribution controller 130. In this case, it is assumed that the determination result is set to be "Yes". In step SA5, the communication block forming unit 150 sets distribution information (e.g., computer program) in the distribution information region 760 shown in Fig. 3, and gives the formed distribution communication block 800 to the collection and distribution controller 130.

In this manner, in step SB2 shown in Fig. 6, the collection and distribution controller 130 calls the transmission processor 170. More specifically, the collection and distribution controller 130 gives the distribution communication block 800 formed by the communication block forming unit 150 to the transmission processor 170. In this manner, in step A1 shown in Fig. 10, the transmission processor 170 of the server 100 transmits the distribution communication block 800 to the relay client 400 through the Internet 200.

When the distribution communication block 800 is received by the reception processor 410 of the relay client 400 shown in Fig. 1, in step A2, the relay client 400 copies distribution information set in the distribution information

region 760 of the distribution communication block 800 shown in Fig. 3, and sets the result of distribution in the result management information region 748₀.

More specifically, in step SD1 shown in Fig. 8, the
5 collection and distribution controller 420 of the relay client 400 calls the reception processor 410 to cause the reception processor 410 to receive the distribution communication block 800. In step SD2, the collection and distribution controller 420 calls the data processor 430 to cause the data processor
10 430 to perform data processing to the distribution communication block 800. In this manner, the data processor 430 copies distribution information set in the distribution information region 760 of the distribution communication block 800 shown in Fig. 3, and then stores the copy in the data storage
15 unit 440.

In step SD3, the collection and distribution controller 420 calls the circulation controller 450. In this manner, in step SE1 shown in Fig. 9, the circulation controller 450 sets "normal" as a result of distribution in the result management
20 information region 748₀ shown in Fig. 3. The circulation controller 450 sets "undistributed" in the collection and distribution management flag 746₀. In step SE2, the circulation controller 450 refers to the circulation information region 740 shown in Fig. 3 and refers to the next
25 circulation destination information 742₁. The circulation

destination information 742₁ is information related to the client 600₁ which is the next circulation destination.

In step SE3, the circulation controller 450 determines whether "undistributed" is set in the collection and
5 distribution management flag 746₁ of the circulation destination information 742₁ which is referred to in step SE2. In this case, the determination result is set to be "Yes". In step SE4, the circulation controller 450 determines whether the distribution communication block 800 can be transmitted
10 to the client 600₁ which is the next circulation destination. In this case, the determination result is set to be "Yes". If the determination result in step SE4 is "No", in step SE7, the circulation controller 450 waits a predetermined period of time on the basis of time measurement by a timer (not shown).
15 In step SE5, the circulation controller 450, for example, uses a ping command or the like to determine whether the client 600₁ which is the next circulation destination operates or not. If the determination result is "No", the circulation controller 450 executes processing subsequent to step SE2
20 related to the client 600₂ which is the next circulation destination. In this case, if the determination result in step SE5 is "Yes", in step SE6, the circulation controller 450 requests of the transmission processor 460 that the distribution communication block 800 is transmitted to the
25 next client 600₁.

In this manner, in step A3 shown in Fig. 10, the transmission processor 460 transmits the distribution communication block 800 to the client 600 through the LAN 500. In parallel to the transmission operation, in step SD4 shown
5 in Fig. 8, the collection and distribution controller 420 determines whether a client in which the collection and distribution controller 420 is incorporated is the relay client 400 or not. In this case, the determination result is set to be "Yes". In step SD5, the collection and distribution
10 controller 420 calls the transmission processor 480. At this time, any information is not transmitted from the transmission processor 480.

In step SD6, the collection and distribution controller 420 transmits the distribution communication block 800 to the
15 server 100 to determine whether a status of distribution is notified or not. In this case, the determination result is set to be "No". In step SD7, the collection and distribution controller 420 calls the reception processor 470. In this manner, the reception processor 470 is set in a reception
20 waiting state. Subsequently, the loop of step SD4 to SD7 is repeated.

When the distribution communication block 800 is received by the reception processor 610 of the client 600₁, in step A4 shown in Fig.10, the client 600₁ copies distribution
25 information set in the distribution information region 760 of

the distribution communication block 800 shown in Fig. 3 to set a result of distribution in the result management information region 748₁.

More specifically, in step SD1 shown in Fig. 8, the
5 collection and distribution controller 620 of the client 600₁ calls the reception processor 610 to cause the reception processor 610 to receive the distribution communication block 800. In step SD2, the collection and distribution controller 620 calls the data processor 630 to cause the data processor
10 630 to perform data processing to the distribution communication block 800. In this manner, the data processor 630 copies distribution information set in the distribution information region 760 of the distribution communication block 800 shown in Fig. 3, and then the copy in the data storage unit
15 640.

In step SD3, the collection and distribution controller 620 calls the circulation controller 650. In this manner, in step SE1 shown in Fig. 9, the circulation controller 650 sets "normal" as a result of distribution in the result management
20 information region 748₁ shown in Fig. 3. The circulation controller 650 sets "distributed" in the collection and distribution management flag 746₁. In step SE2, the circulation controller 650 refers to the circulation information region 740 shown in Fig. 3 and refers to the next
25 circulation destination information (not shown). The

circulation destination information is information related to the client 600, which is the next circulation destination.

In step SE3, the circulation controller 650 determines whether "undistributed" is set as a collection and distribution flag of the circulation destination information which is referred to in step SE2. In this case, the determination result is set to be "Yes". In step SE4, the circulation controller 650 determines whether the distribution communication block 800 can be transmitted to the client 600, which is the next circulation destination. In this case, the determination result is set to be "Yes". If the determination result in step SE4 is "No", in step SE7, the circulation controller 650 waits a predetermined period of time on the basis of time measurement by the timer.

In step SE5, the circulation controller 650, for example, uses a ping command or the like to determine whether the client 600, which is the next circulation destination operates or not. If the determination result is "No", the circulation controller 650 executes processing subsequent to step SE2 related to the client 600, which is the next circulation destination. In this case, if the determination result in step SE5 is "Yes", in step SE6, the circulation controller 650 requests of the transmission processor 660 that the distribution communication block 800 is transmitted to the next client 600.

In this manner, in step A5 shown in Fig. 10, the transmission processor 660 transmits the distribution communication block 800 to the client 600₂ through the LAN 500. In parallel to the transmission operation, in step SD4 shown in Fig. 8, the collection and distribution controller 620 determines whether a client in which the collection and distribution controller 620 is incorporated is the relay client 400 or not. In this case, the determination result is set to be "No".

10 Thereafter, in steps subsequent to step A6 shown in Fig. 10, by the same operation as described above, copying of distribution information, setting of a result, and transmission (circulation) of the distribution communication block 800 to a client which is the next circulation destination are sequentially performed. When the distribution communication block 800 is received by the client 600_n which is the final circulation destination, in step A8, the client 600_n copies distribution information and sets a result in the same operation as described above. In step A9, the client 600_n transmits the distribution communication block 800 to the relay client 400 through the LAN 500.

When the distribution communication block 800 is received by the reception processor 470 of the relay client 400 in step SD7 shown in Fig. 8, the collection and distribution controller 420 sets the determination result in step SD4 to

be "Yes", and then gives the distribution communication block 800 to the transmission processor 480 in step SD5. In this manner, in step A10 shown in Fig. 10, the transmission processor 480 transmits the distribution communication block 800 to the server 100 through the Internet 200. In addition, the collection and distribution controller 420 sets the determination result in step SD6 to be "Yes" to end the series of processes.

When the distribution communication block 800 is received by the reception processor 180 of the server 100, in step SB3 shown in Fig. 6, the collection and distribution controller 130 calls the result management unit 190. In this manner, in step SC1 shown in Fig. 7, the result management unit 190 receives the distribution communication block 800. In step SC2, the result management unit 190 decides the type of the collection and distribution ID 720 (see Fig. 3) of the distribution communication block 800.

In this case, since the collection and distribution ID 720 is a collection and distribution ID for normal collection and distribution, in step SC3, the result management unit 190 holds results of distribution (normal or abnormal) with reference to result management information regions 478₀ to 478_n of the pieces of circulation destination information 742₀ to 742_n of the distribution communication block 800. In step SC4, the result management unit 190 increments a result distributed

counter (not shown) by the number of times which the results are normal.

As a result, the result distributed counter is to count clients to which pieces of information are normally distributed in the series of distribution processes for the relay client 400 and the clients 600_1 to 600_n . In this case, the count value of the result distributed counter is set at $n + 1$. More specifically, the pieces of distribution information are distributed to all the relay client 400 and the clients 600_1 to 600_n .

In step SC5, the result management unit 190 determines whether the count result (in this case, $n + 1$) of the result distributed counter is equal to the number of all clients (in this case, $n + 1$) or not. In this case, the determination result is set to be "Yes" to end the series of processes. When the collection and distribution ID 720 is a collection and distribution ID for canceling, in step SC6, the result management unit 190 clears the result of distribution set in the result management information region of the distribution communication block.

A collection operation in Operational Example 1 of the first embodiment will be described below with reference to Fig. 5 to Fig. 9 and Fig. 11. In the following description, a case in which pieces of collection information are collected from the relay client 400 and the clients 600_1 to 600_n by a circulation

system using the collection communication block 900 shown in Fig. 4. In step SB1 shown in Fig. 6, the collection and distribution controller 130 of the server 100 calls the communication block forming unit 150.

5 In this case, when collection processing is designated by the collection and distribution controller 130, in step SA6 shown in Fig. 5, the communication block forming unit 150 forms the collection communication block 900 formed from the basic communication block 700 (see Fig. 2) and shown in Fig. 4, and
10 then sets the collection and distribution ID 720 for normal collection and distribution in the collection communication block 900.

 In step SA7, the communication block forming unit 150, as destinations of circulation using the collection
15 communication block 900, all the relay client 400 and the clients 600₁ to 600_n shown in Fig. 1 are set. In step SA4, the communication block forming unit 150 determines whether distribution processing is performed by the control of the collection and distribution controller 130 or not. In this
20 case, since collection processing is performed, the communication block forming unit 150 sets the determination result to be "No" and gives the formed collection communication block 900 to the collection and distribution controller 130.

 In this manner, in step SB2 shown in Fig. 6, the
25 collection and distribution controller 130 gives the

collection communication block 900 formed by the communication block forming unit 150 to the transmission processor 170 to make a transmission request. In this manner, in step B1 shown in Fig. 11, the transmission processor 170 of the server 100
5 transmits the collection communication block 900 to the relay client 400 through the Internet 200.

When the collection communication block 900 is received by the reception processor 410 of the relay client 400 shown in Fig. 1, in step B2, the relay client 400 sets collection
10 information in the collection information region 780 of the collection communication block 900 shown in Fig. 4, and sets a result of collection (in this case, normal) in the result management information region 748.

More specifically, in step SD1 shown in Fig. 8, the
15 collection and distribution controller 420 of the relay client 400 calls the reception processor 410 to cause the reception processor 410 to receive the collection communication block 900. In step SD2, the collection and distribution controller 420 calls the data processor 430 to cause the data processor
20 430 to perform data processing to the collection communication block 900. In this manner, the data processor 430 sets collection information in the collection information region 780 of the collection communication block 900 shown in Fig. 4.

25 In step SD3, the circulation controller 450 is called.

In this manner, in step SE1 shown in Fig. 9, the circulation controller 450 sets collection information in the collection information 783, shown in Fig. 4, and sets "normal" as a result of collection in the result management information region 748.

- 5 In step SE2, the circulation controller 450 refers to the circulation information region 740 shown in Fig. 4 and refers to the next circulation destination information 742₁. The circulation destination information 742₁ is information related to the client 600₁ which is the next circulation
- 10 destination.

In step SE3, the circulation controller 450 determines whether "uncollected" is set in the collection and distribution management flag 746₁ of the circulation destination information 742₁ which is referred to in step SE2.

- 15 In this case, the determination result is set to be "Yes". In step SE4, the circulation controller 450 determines whether the collection communication block 900 can be transmitted to the client 600₁ which is the next circulation destination. In this case, the determination result is set to be "Yes". If
- 20 the determination result in step SE4 is "No", in step SE7, the circulation controller 450 waits a predetermined period of time on the basis of time measurement by the timer.

- In step SE5, the circulation controller 450, for example, uses a ping command or the like to determine whether the client
- 25 600₁ which is the next circulation destination operates or not.

If the determination result is "No", the circulation controller 450 executes processing subsequent to step SE2 related to the client 600₂ which is the next circulation destination. In this case, if the determination result in step SE5 is "Yes", in step SE6, the circulation controller 450 requests of the transmission processor 460 that the collection communication block 900 is transmitted to the next client 600₁.

In this manner, in step B3 shown in Fig. 11, the transmission processor 460 transmits the collection communication block 900 to the client 600 through the LAN 500. In parallel to the transmission operation, in step SD4 shown in Fig. 8, the collection and distribution controller 420 determines whether a client in which the collection and distribution controller 420 is incorporated is the relay client 400 or not. In this case, the determination result is set to be "Yes". In step SD5, the collection and distribution controller 420 calls the transmission processor 480. At this time, any information is not transmitted from the transmission processor 480.

In step SD6, the collection and distribution controller 420 transmits the collection communication block 900 to the server 100 to determine whether a status of collection is notified or not. In this case, the determination result is set to be "No". In step SD7, the collection and distribution controller 420 calls the reception processor 470. In this

manner, the reception processor 470 is set in a reception waiting state. Subsequently, the loop of step SD4 to SD7 is repeated.

When the collection communication block 900 is received
5 by the reception processor 610 of the client 600₁, in step B4,
as in step B2, the client 600₁ sets collection information in
the collection information region 780 of the collection
communication block 900 shown in Fig. 4 and sets a result of
collection in the result management information region 748₁.
10 More specifically, in step SD1 shown in Fig. 8, the
collection and distribution controller 620 of the client 600₁
calls the reception processor 610 to cause the reception
processor 610 to receive the collection communication block
900. In step SD2, the collection and distribution controller
15 620 calls the data processor 630 to cause the data processor
630 to perform data processing to the collection communication
block 900. In this manner, the data processor 630 sets
collection information in the collection information region
780 of the collection communication block 900 shown in Fig.
20 4.

In step SD3, the circulation controller 650 is called.
In this manner, in step SE1 shown in Fig. 9, the circulation
controller 650 sets "collected" as a result of collection in
the result management information region 748₀ shown in Fig.
25 4. In step SE2, the circulation controller 650 refers to the

circulation information region 740 shown in Fig. 4 and refers to the next circulation destination information (not shown). The circulation destination information is information related to the client 600₂, which is the next circulation
5 destination.

In step SE3, the circulation controller 650 determines whether "uncollected" is set as the collection and distribution flag 746₁ of the circulation destination information which is referred to in step SE2. In this case,
10 the determination result is set to be "Yes". In step SE4, the circulation controller 650 determines whether the collection communication block 900 can be transmitted to the client 600₂, which is the next circulation destination. In this case, the determination result is set to be "Yes". If the determination
15 result in step SE4 is "No", in step SE7, the circulation controller 650 waits a predetermined period of time on the basis of time measurement by the timer.

In step SE5, the circulation controller 650, for example, uses a ping command or the like to determine whether the client
20 600₂, which is the next circulation destination operates or not. If the determination result is "No", the circulation controller 650 executes processing subsequent to step SE2 related to the client 600₃, which is the next circulation destination. In this case, if the determination result in step
25 SE5 is "Yes", in step SE6, the circulation controller 650

requests of the transmission processor 660 that the collection communication block 900 is transmitted to the next client 600₂.

In this manner, in step B5 shown in Fig. 11, the transmission processor 460 transmits the collection communication block 900 to the client 600₂ through the LAN 500. In parallel to the transmission operation, in step SD4 shown in Fig. 8, the collection and distribution controller 620 determines whether a client in which the collection and distribution controller 620 is incorporated is the relay client 400 or not. In this case, the determination result is set to be "No".

Thereafter, in steps subsequent to step B6 shown in Fig. 11, by the same operation as described above, setting of collection information, setting of a result, and transmission (circulation) of the collection communication block 900 to a client which is the next circulation destination are sequentially performed. When the collection communication block 900 is received by the client 600_n which is the final circulation destination, in step B8, the client 600_n performs setting of collection information and setting of a result by the same operation as described above. In step B9, the client 600_n transmits the collection communication block 900 to the relay client 400 through the LAN 500.

When the collection communication block 900 is received by the reception processor 470 of the relay client 400 in step

SD7 shown in Fig. 8, the collection and distribution controller 420 sets the determination result in step SD4 to be "Yes", and then gives the collection communication block 900 to the transmission processor 480 in step SD5. In this manner, in
5 step B10 shown in Fig. 11, the transmission processor 480 transmits the collection communication block 900 to the server 100 through the Internet 200. In addition, the collection and distribution controller 420 sets the determination result in step SD6 to be "Yes" to end the series of processes.

10 When the collection communication block 900 is received by the reception processor 180 of the server 100, in step SB3 shown in Fig. 6, the collection and distribution controller 130 calls the result management unit 190. In this manner, in step SC1 shown in Fig. 7, the result management unit 190
15 receives the collection communication block 900. In step SC2, the result management unit 190 decides the type of the collection and distribution ID 720 (see Fig. 4) of the collection communication block 900.

In this case, since the collection and distribution ID
20 720 is a collection and distribution ID for normal collection and distribution, in step SC3, the result management unit 190 holds results of distribution (collected or uncollected) with reference to result management information regions 478₀ to 478_n of the pieces of circulation destination information 742₀ to
25 742_n of the collection communication block 900. In step SC4,

the result management unit 190 increments a result distributed counter by the number of times which the results are collected.

In this case the count value of the result collected counter is set to be $n + 1$. More specifically, pieces of
5 collection information are normally collected from all the relay client 400 and the clients 600_1 to 600_n . In step SC5, the result management unit 190 determines whether the count result (in this case, $n + 1$) of the result collected counter is equal to the number of all clients (in this case $n + 1$).
10 In this case, the determination result is set to be "Yes" to end the series of processes.

In the distribution operation described with reference to Fig. 10, if the determination result of step SC5 shown in Fig. 7 is "No", that is, if a result of distribution of the
15 relay client 400 and the clients 600_1 to 600_n is "abnormal", a retry distribution operation (see Fig. 12) which distribution information is distributed to the "abnormal" client again is performed.

More specifically, when the communication block forming
20 unit 150 is called by the collection and distribution controller 130 of the server 100 in step SB1 shown in Fig. 6, in step SA1 shown in Fig. 5, the communication block forming unit 150 determines a processing type (normal collection and distribution processing, retry distribution processing, and
25 cancel processing).

In this case, it is assumed that the retry distribution processing is designated by the collection and distribution controller 130. At this time, in step SA2, the communication block forming unit 150 forms a retry distribution communication block (not shown) shown in Fig. 3 from the basic communication block 700 (see Fig. 2), and then sets the collection and distribution ID 720 for retry in the retry distribution communication block. The basic data structure of the retry distribution communication block is the same as that of the distribution communication block 800 (see Fig. 3). Therefore, the retry distribution communication block will be described below with reference to the distribution communication block 800.

In step SA3, the communication block forming unit 150 resets a circulation destination information a result of distribution of which is "abnormal" in the circulation destination information 742₀ to 742_n shown in Fig. 3. In this case, it is assumed that the results of distribution related to the relay client 400 and the clients 600₃ to 600_{n-1} (not shown) are "normal". On the other hand, it is assumed that the results of distribution of the clients 600₁, 600₂, and 600_n are "abnormal".

In step SA4, the communication block forming unit 150 determines whether (retry) distribution processing is performed by the control of the collection and distribution

controller 130 or not. In this case, the decision result is set to be "Yes". In step SA5, the communication block forming unit 150 sets distribution information in the distribution information region 760 shown in Fig. 3, and gives a formed retry distribution communication block to the collection and distribution controller 130.

In this manner, in step SB2 shown in Fig. 6, the collection and distribution controller 130 calls the transmission processor 170. More specifically, the collection and distribution controller 130 gives a retry distribution communication block formed by the communication block forming unit 150 to the transmission processor 170 to make a transmission request. In this manner, in step C1 shown in Fig. 12, the transmission processor 170 of the server 100 transmits the retry distribution communication block to the relay client 400 through the Internet 200.

When the retry distribution communication block is received by the reception processor 410 of the relay client 400 shown in Fig. 1, in step C2, the relay client 400 relays the retry distribution communication block to the client 600. More specifically, in step C3, since the relay client 400 has received distribution information, the retry distribution communication block is transmitted to the client 600 (abnormal).

When the retry distribution communication block is

received by the client 600₁, in step C4, the client 600₁ copies distribution information set in the distribution information region 760 of the retry distribution communication block shown in Fig. 3 and sets a result of distribution in the result management information region 748₁. In step C5, the client 600₁ transmits the retry distribution communication block to the client 600₂ (abnormal).

When the retry distribution communication block is received by the client 600₂, in step C6, the client 600₂ copies distribution information set in the distribution information region 760 of the retry distribution communication block shown in Fig. 3 and sets a result of distribution in the result management information region 748₁. In step C6, the client 600₂ transmits the retry distribution communication block to the client 600_a (abnormal).

When the retry distribution communication block is received by the client 600_a, in step C8, the client 600_a performs copying of distribution information and setting of a result by the same operation as described above. In step C9, the client 600_a transmits the retry distribution communication block to the relay client 400 through the LAN 500.

When the retry distribution communication block is received by the relay client 400 in step SD7 shown in Fig. 8 in step C10, the collection and distribution controller 420 causes the relay client 400 to the server 100 transmit the retry

distribution communication block to through the Internet 200.

When the retry distribution communication block is received by the reception processor 180 of the server 100, in the result management unit 190, processing related to the retry
5 distribution communication block is executed according to the flow chart shown in Fig. 7. Although the retry distribution operation has been described above, a retry operation may be performed in case of collection by the same operation as the retry distribution operation.

10 In Operational Example 1 of the first embodiment described above, the following example has been described. That is, in a distribution operation (see Fig. 10) or a collection operation (see Fig. 11), when the distribution communication block 800 or the collection communication block
15 900 is received by the client 600_n which is the final circulation distribution, the distribution communication block 800 or the collection communication block 900 is transmitted to the server 100 through the relay client 400, so that a result of collection and distribution is notified. However, the result
20 of collection and distribution is intermediately notified in the middle of collection and distribution. This case will be described below as Operational Example 2 of the first embodiment.

Operational Example 2 of the first embodiment will be
25 described below with reference to Figs. 13 and 14. Fig. 14

is a sequence diagram for explaining a distribution operation in Operational Example 2 of the first embodiment. A collection operation which performs intermediate notification is also performed by the same manner as that of the distribution operation (to be described later).

In step D1 shown in Fig. 14, the server 100 transmits the distribution communication block 800 to the relay client 400 through the Internet 200. When the distribution communication block 800 is received by the relay client 400 shown in Fig. 1, in step D2, the relay client 400 copies distribution information set in the distribution information region 760 of the distribution communication block 800 and sets a result of distribution in the result management information region 748, as in Operational Example 1.

More specifically, in step SF1 shown in Fig. 13, the circulation controller 450 of the relay client 400 sets "normal" as a result of distribution in the result management information region 748, shown in Fig. 3. In step SF2, the circulation controller 450 refers to the circulation information region 740 shown in Fig. 3 and refers to the next circulation destination information 742₁. In step SF3, the circulation controller 450 determines whether "undistributed" in the collection and distribution management flag 746₁ of the circulation destination information 742₁ which is referred to in step SF2 or not. In this case, the determination result

is set to be "Yes".

In step SF4, the circulation controller 450 determines whether the distribution communication block 800 is transmitted to the client 600₁ which is the next circulation
5 destination or not. In this case, the determined result is set to be "Yes". In step SF5, the circulation controller 450 uses, for example, uses a ping command or the like to determine whether the client 600₁ which is the next circulation destination operates or not. In this case, the determination
10 result is set to be "Yes".

In step SF6, the circulation controller 450 requests of the transmission processor 460 that the distribution communication block 800 is transmitted to the next client 600₁. In this manner, in step D3 shown in Fig. 14, the transmission
15 processor 460 transmits the distribution communication block 800 to the client 600₁ through the LAN 500.

When the distribution communication block 800 is received by the reception processor 610 of the client 600₁, in step D4 shown in Fig. 14, the client 600₁ copies distribution
20 information set in the distribution information region 760 of the distribution communication block 800 shown in Fig. 3 and sets a result of distribution in the result management information region 748₁. In step D5, the client 600₁ transmits the distribution communication block 800 to the client 600₂
25 through the LAN 500.

When the distribution communication block 800 is received by a reception processor (not shown) of the client 600₂, in step D6, the client 600₂ copies distribution information set in the distribution information region 760 of the distribution communication block 800 shown in Fig. 3 and sets a result of distribution in the result management information region 748₂ (not shown).

More specifically, in step SF1 shown in Fig. 13, the circulation controller (not shown) of the client 600₂ sets "normal" as a result of distribution in the result management information region of the distribution communication block 800. In step SF2, the circulation controller 650 refers to the circulation information region 740 shown in Fig. 3 and refers to next circulation destination information (not shown). This circulation destination information is information related to the client 600₃ (not shown) which is the next circulation destination.

In step SF3, the circulation controller determines whether "undistributed" in the collection and distribution management flag of the circulation destination information which is referred to in step SF2 or not. In this case, the determination result is set to be "Yes". In step SF4, the circulation controller determines whether the distribution communication block 800 can be transmitted to the client 600₃ (not shown) which is the next circulation destination. In this

case, if the client 600₁ is defective, the circulation controller sets the determination result in step SF4 to be "No".

In step SF7, the circulation controller copies the distribution communication block 800. In step SF8, the circulation controller requests of the transmission processor 460 that the distribution communication block 800 for intermediate notification is transmitted to the relay client 400. In this manner, in step SD7 shown in Fig. 14, the transmission processor of the client 600₂ transmits the distribution communication block 800 for intermediate notification to the relay client 400 through the LAN 500.

When the distribution communication block 800 for intermediate notification is received by the relay client 400, in step D8, the relay client 400 transmits the distribution communication block 800 to the server 100 through the Internet 200. In this manner, intermediate notification of a result of distribution is performed to the server 100 through the operation described above.

In step SF9 shown in Fig. 13, the circulation controller of the client 600₂ waits a predetermined period of time. In step SF5, the circulation controller, for example, uses a ping command or the like to determine whether the client 600, which is the next circulation destination operates or not. In this case, the determination result is set to be "No", the circulation controller executes processes subsequent to step

SF2 related to the client 600₄, which is the next circulation destination.

In this case, if the determination result in step SF5 is "Yes", in step SF6, the circulation controller requests of the transmission processor that the distribution communication block 800 is transmitted to the client 600₃. Thereafter, in step D9 to step D12 shown in Fig. 14, the same processes as those in step A7 to step A10 shown in Fig. 10 are performed.

In Operational Example 1 of the first embodiment described above, the case in which one distribution communication block 800 (or collection communication block 900) is transmitted to one group constituted by the relay client 400 shown in Fig. 1 and the clients 600₁ to 600_n has been explained. However, as shown in Fig. 15, the relay client 400 and the clients 600₁ to 600_n may be partitioned into groups G₁ to G_x, and collection and distribution may be performed to each group. This case will be described below as Operational Example 3 of the first embodiment.

The group G₁ shown in Fig. 15 is constituted by clients 600₁ to 600_h belonging to a segment SG₁ of the LAN 500. A group G₂ is constituted by clients 600_i (i > h) to 600_j (j > i) belonging to a segment SG₂. A group G_x is constituted by clients 600_k (k > j) to 600_n (n > k) belonging to a segment SG_x. In this example, the number of partitions (the number of groups) of

a relay client 400 and the clients 600₁ to 600_n is x.

In the arrangement described above, when the distribution communication block 800 (see Fig. 18A) is formed by the communication block forming unit 150 of the server 100 shown in Fig. 15, in step E1 shown in Fig. 19, the transmission processor 170 of the server 100 transmits the distribution communication block 800 to the relay client 400 through the Internet 200.

When the distribution communication block 800 is received by the reception processor 410 of the relay client 400 shown in Fig. 1, in step E2, the relay client 400 copies distribution information and sets the result of distribution. In step E3, the relay client 400 forms partition distribution communication blocks 800₁ to 800_n shown in Fig. 18B to Fig. 18D.

More specifically, the collection and distribution controller 420 of the relay client 400 calls the data processor 430 to cause the data processor 430 to perform data processing to the distribution communication block 800. In this manner, the data processor 430 copies distribution information set in the distribution information region 760 of the distribution communication block 800 shown in Fig. 18A, and then stores the copy in the data storage unit 440.

The collection and distribution controller 420 calls the circulation controller 450. In this manner, in step SG1 shown in Fig. 16, the circulation controller 450 of the relay client

400 determines whether partition distribution is designated by the collection and distribution controller 420 or not. If the determination result is "No", in step SG16, the circulation controller 450 executes normal distribution processing which is the same as that in Operational Example 1 of the first embodiment. In step SG17, the circulation controller 450 calls the reception processor 470.

In this case, when partition distribution is designated by the collection and distribution controller 420, in step SG2, the circulation controller 450 sets "normal" as a result of distribution in the result management information region 748, shown in Fig. 3. The process in step SG1 is the same as the process in step SE1 (see Fig. 9). In step SG3, the circulation controller 450 calls the partition processor 490.

In this manner, in step SH1 shown in Fig. 17, the partition processor 490 forms the partition distribution communication blocks 800_1 to 800_x shown in Figs. 18B to 18D from the distribution communication block 800 shown in Fig. 18A by copy. Each of the data structures of the partition distribution communication blocks 800_1 to 800_x is the same as the data structure of the distribution communication block 800. The partition distribution communication blocks 800_1 to 800_x correspond to groups G_1 to G_x belonging to segments SG_1 to SG_x shown in Fig. 15. In step SG2, the partition processor 490 refers to the circulation information region 740 (see Fig. 3)

of the distribution communication block 800.

In step SH3, the partition processor 490 sets circulation destination information in the circulation information region 740₁ of the partition distribution communication block 800₁ on the basis of a partition condition designated by the collection and distribution controller 420. The partition condition mentioned here is that the clients 600₁ to 600_n shown in Fig. 15 are partitioned into groups G₁ to G_k. For this reason, in the circulation information region 740₁ of the partition distribution communication block 800₁ shown in Fig. 18B, pieces of circulation destination information (client names, addresses, and the like) related to the clients 600₁ to 600_n in the group G₁ shown in Fig. 15.

In step SH4, the partition processor 490 determines whether partition is completed or not. In this case, the determination result is set to be "No". Thereafter, the processes in step SH2 and SH3 are repeated. In this manner, in the circulation information region 740₂ of the partition distribution communication block 800₂ (see Fig. 18C), pieces of circulation destination information (client names, addresses, and the like) related to clients 600₁ to 600_j in the group G₂ are set. In the same manner as described above, pieces of circulation destination information (client names, addresses, and the like) related to the clients 600_k to 600_n in the group G_k shown in Fig. 18D are set in the circulation

information region 740_x of the partition distribution communication block 800_x (see Fig. 18D).

When the determination result in step SH4 becomes "Yes", the partition processor 490 copies the distribution information set in the distribution information region 760 (see Fig. 18A) of the distribution communication block 800 to the distribution information regions 760 of the partition distribution communication blocks 800₁ to 800_x, respectively.

In step SG4 shown in Fig. 16, the circulation controller 450 refers to the partition distribution communication block 800₁ (see Fig. 18B). In step SG5, the circulation controller 450 checks the operation of a circulation destination (in this case, the client 600₁) which is set first in the circulation information region 740₁ to perform monitoring with a timer.

15 In step SG5, the circulation controller 450 calls the transmission processor 460 and requests of the transmission processor 460 that the partition distribution communication block 800₁ is transmitted to the client 600₁. In this manner, the transmission processor 460 transmits the partition distribution communication block 800₁ to the client 600₁ through the LAN 500 (step E3: see Fig. 19).

In step SG7, the circulation controller 450 increments a transmission counter for counting the number of transmitted partition distribution communication blocks by 1. In step SG8, it is determined whether the count value of the transmission

counter is equal to the number of partitions (in this case, x) or not. In this case, the determination result is set to be "No".

Thereafter, when the processes in step SG4 to step SG7
5 are repeated, the partition distribution communication blocks $800_2, \dots, 800_x$ are transmitted from the transmission processor 460 of the relay client 400 to the clients $600_1, \dots, 600_k$, respectively, (step E4: see Fig. 19). When the determination result in step SG8 becomes "Yes", in step SG9, the relay client
10 400 calls the reception processor 470 to set in a reception waiting state.

When the partition distribution communication block 800_1 is received by the client 600_1 , in step E5 shown in Fig. 19, the client 600_1 copies the distribution information set in the
15 distribution information region 760 of the partition distribution communication block 800_1 shown in Fig. 18B and sets a result of distribution in a result management information region (not shown). In step E6, the client 600_1 transmits the partition distribution communication block 800_1
20 to the client 600_2 .

Thereafter, the partition distribution communication block 800_1 is sequentially circulated. When the partition distribution communication block 800_1 is received by the client 600_n which is the final circulation destination in the group
25 G_1 , in step E7, the client 600_n copies the distribution

information and sets a result. In step E8, the client 600_n transmits the partition distribution communication block 800₁ to the relay client 400 through the LAN 500.

In parallel to the processes in steps E5 to E8 described above, the processes in step E9 to step E12 are executed in the group G₂, and the processes in step E13 to step E16 in the group G_x. In this manner, the partition distribution communication blocks 800₂ and 800_x are transmitted from the clients 600_j and 600_x to the relay client 400.

When the partition distribution communication blocks 800₁ to 800_x are received by the relay client 400, in step E17, the relay client 400 merges the partition distribution communication blocks 800₁ to 800_x. More specifically, the partition distribution communication block 800₁ is received by the reception processor 470, in step SG10 shown in Fig. 16, the circulation controller 450 increments a received counter for counting received distribution communication blocks by 1.

In step SG11, the circulation controller 450 refers to a result of distribution related to the group G₁ from the circulation destination information 742₁ (see Fig. 18B) of the partition distribution communication block 800₁. In step SG12, the circulation controller 450 sets a result of distribution related to the group G₁ in the circulation information region 740 (see Fig. 18A) of the distribution communication block 800.

In step SG13, the circulation controller 450 determines

whether collection processing is performed or not. In this case, the determination is set to be "No". If the determination result in step SG13 is "No", in step SG14, the circulation controller 450 sets collection information 5 related to the group G_i in the collection communication block.

In step SG15, the circulation controller 450 determines whether the count result of the received counter is equal to the number of partitions ($= x$). In this case, the determination result is set to be "No". Thereafter, each time 10 the partition distribution communication blocks 800_i to 800_x are received by the reception processor 470, the processes in step SG9 to step SG12 described above are executed. When merging related to all the partition distribution communication blocks 800_i to 800_x is completed, the circulation 15 controller 450 sets the determination result in step SG15 to be "Yes".

In this manner, in step E18 shown in Fig. 19, the relay client 400 transmits the distribution communication block 800 (see Fig. 18A) to the server 100 through the Internet 200. 20 Thereafter, as in Operational Example 1 of the first embodiment, result management (see Fig. 7) is executed by the result management unit 190.

As has been described above, according to the first embodiment, when the relaying function is given to the relay 25 client 400, and circulation of all the distribution

communication blocks 800 (or collection communication blocks 900) is completed, the distribution communication block 800 (or collection communication block 900) to the server 100 in which a distribution result (or collection result) is set is
5 relayed through the relay client 400. For this reason, unlike a conventional technique, the dedicated server 40 (see Fig. 24) need not be arranged, and, by performing distribution once, the distribution communication block 800 (or collection communication block 900) may be transmitted from the LAN 500
10 to the Internet 200 once. For this reason, a network load can be reduced with a low cost and a high security.

According to the first embodiment, when the relaying function is given to the relay client 400, and circulation of all the distribution communication blocks 800 is completed,
15 the distribution communication block 800 to the server 100 in which a distribution result is set is relayed through the relay client 400. For this reason, unlike a conventional technique, the dedicated server 40 (see Fig. 24) need not be arranged, and, by performing distribution once, the distribution
20 communication block 800 may be transmitted from the LAN 500 to the Internet 200 once. For this reason, a network load can be reduced with a low cost and a high security.

In addition, according to the first embodiment, a client which fails in distribution (or collection) is recognized on
25 the basis of a distribution result (or collection result) set

in the distribution communication block 800 (or collection communication block 900) related to the first distribution (or collection), and a retry distribution communication block (or retry collection communication block) is retransmitted to the
5 client. For this reason, reliability related to distribution (or collection) can be improved.

According to the first embodiment, when the client which is the next circulation destination is stopped in the middle of circulation of the distribution communication block 800 (or
10 collection communication block 900), as intermediate notification, the distribution communication block 800 (or collection communication block 900) is relayed from the client to the server 100. For this reason, on the server 100 side, a distribution result (or collection result) can be quickly
15 recognized without waiting for the distribution communication block 800 (or collection communication block 900) from the client 600_n which is the final circulation destination.

According to the first embodiment, the relay client 400 and the clients 600₁ to 600_n are grouped into the groups G₁ to G_x, and communication blocks are circulated in each of the
20 groups. For this reason, time required for distribution (or collection) can be shortened.

Fig. 20 is a block diagram showing the configuration of a second embodiment according to the present invention. The
25 configuration of the second embodiment shown in Fig. 20 is the

concrete example of the first embodiment described above. Therefore, the operation of the second embodiment is the same as the operation of the first embodiment.

In Fig. 20, a main office network system 1000 is an
5 in-house system installed in a main office, and is constituted by a main office server 1010, a LAN 1030, and a fire wall 1040. The main office server 1010 has a function of distributing pieces of information (e.g., an application program 1020) to an employee 0 client 1230₀, to an employee n client 1230_n, and
10 a function of collecting pieces of information from the employee 0 client 1230₀, to the employee n client 1230_n. The configuration and operation of the main office server 1010 are the same as the configuration and operation of the server 100 (see Fig. 1).

15 The main office server 1010 is connected to the LAN 1030. The fire wall 1040 is to prevent illegal access from an external system to the main office network system 1000, and is designed to cause only pieces of information or protocols to which securities are given to pass. The LAN 1030 is an in-house
20 network installed in the main office, and is connected to Internet 1100 through the fire wall 1040.

A branch office network system 1200 is an in-house system installed in a branch office, and is constituted by a fire wall 1210, a LAN 1220, and an employee 0 client 1230₀, to an employee
25 n client 1230_n. The fire wall 1210, like the fire wall 1040,

is to prevent illegal access to the branch office network system 1200.

The LAN 1220 is an in-house network installed in a branch office, and is connected to the Internet 1100 through the fire wall 1210. The employee 0 client 1230₀ to the employee n client 1230_n are computers corresponding to an employee 0 to an employee n (not shown) in the branch office, and are connected to the LAN 1220. The configuration and operation of the employee 0 client 1230₀ are the same as the configuration and operation of the relay client 400 (see Fig. 1). The configuration and operation of the employee 1 client 1230₁ to the employee n client 1230_n are the same as the configuration and operation of the clients 600₁ to 600_n (see Fig. 1).

In this case, in the second embodiment, a distribution communication block 1300 shown at (a) in Fig. 21 is used. The data structure of the distribution communication block 1300 is the same as that of the distribution communication block 800 (see Fig. 3). Therefore, the same reference numerals as in Fig. 3 denote the same parts in Figs. 21A and 21B. The pieces of circulation destination information 742₀ to 742_n shown at (b) in Fig. 21 correspond to the employee 0 client 1230₀ to the employee n client 1230_n.

For example, as shown at (c) in Fig. 21, the circulation destination information 742₀ is constituted by pieces of information, i.e., an "employee" (client name 743₀),

"123.456.789.001" (address 744₀), "undistributed" (collection and distribution management flag 746₀), and "undefined" (result management information region 748₀).

When the distribution communication block 1300 having
5 the circulation information region 740 shown at (c) in Fig.
21 is transmitted to the employee 0 client 1230₀, as shown at
(d) in Fig. 21, transition from "undistributed" to
"distributed" occurs in the collection and distribution
management flag 746₀, and transition from "undefined" to
10 "normal" occurs in the result management information region
748₀. In addition, when the distribution communication block
1300 is transmitted to the employee 1 client 1230₁ which is
the next circulation destination, as shown at (e) in Fig. 21,
transition from "undistributed" to "distributed" occurs in the
15 collection and distribution management flag 746₁, and
transition from "undefined" to "normal" occurs in the result
management information region 748₁. Thereafter, the
distribution communication block 1300 is sequentially
circulated to the employee 2 client 1230₂ to the employee n
20 client 1230_n.

When the distribution communication block 1300 is
transmitted to the employee n client 1230_n which is the final
circulation destination, as shown at (f) in Fig. 21, transition
from "undistributed" to "distributed" occurs in a collection
25 and distribution management flag 746_n, and transition from

"undefined" to "normal" occurs in the result management information region 748_n.

5 The first and second embodiments according to the present invention have been described above with reference to the drawings. However, a concrete configuration is not limited to the first and second embodiments, and the invention also includes inventions which change in design without departing from the spirit and scope of the invention. For example, in the first and second embodiments, the following
10 configuration may be used. That is, an information collection and distribution program for realizing the collection and distribution function is recorded on a computer readable recording medium, and the information collection and distribution program recorded on the recording medium is
15 loaded on a computer and executed, so that collection and distribution of information are realized.

The computer is constituted by a CPU for executing the information collection and distribution program, an input device such as a keyboard or a mouse, a ROM (Read Only Memory)
20 for storing various data, and a RAM (Random Access Memory) for storing an operation parameter or the like, a reading device for read the information collection distribution program from a recording medium, an output device such as a display or a printer, and a bus BU for connecting the devices to each other.
25 The CPU loads the information collection and

distribution program recorded on the recording medium through the reading device and then executes the information collection and distribution program to perform the collection and distribution. The recording medium includes not only a portable recording medium such as an optical disk, a floppy disk, or a hard disk, but also a transmission medium which temporarily records and holds data like a network.

As has been described above, according to the present invention, when a relaying function is given to one client of a plurality of clients, and circulation of all communication blocks is completed, a communication block in which a distribution result is set is relayed to a server through one server. For this reason, unlike a conventional technique, a dedicated server need not be arranged, and, by performing distribution once, a communication block may be transmitted from an in-house network to an external network once. Therefore, a network load can be advantageously reduced with a low cost and a high security.

Furthermore, a client which fails in distribution is recognized on the basis of a distribution result in a communication block related to the first distribution, so that the communication block is re-transmitted to the client. For this reason, the reliability of distribution can be advantageously improved.

In the middle of circulation of a communication block,

when the client of the next circulation destination is stopped,
as intermediate notification, the communication block from the
client is relayed to a server. For this reason, on the server
side, a distribution result can be quickly recognized without
5 waiting for the communication block from the client of the final
circulation destination.

A plurality of clients are grouped, and communication
blocks are parallel circulated in the groups. For this reason,
time required for distribution can be advantageously
10 shortened.

When a relaying function is given to one client of a
plurality of clients, and circulation of all communication
blocks is completed, a communication block in which a
collection result is set is relayed to a server through one
15 server. For this reason, unlike a conventional technique, a
dedicated server need not be arranged, and, by performing
collection once, a communication block may be transmitted from
an in-house network to an external network once. Therefore,
a network load can be advantageously reduced with a low cost
20 and a high security.

Furthermore, a client which fails in collection is
recognized on the basis of a collection result in a
communication block related to the first collection, so that
the communication block is re-transmitted to the client. For
25 this reason, the reliability of collection can be

advantageously improved.

In the middle of circulation of a communication block, when the client of the next circulation destination is stopped, as intermediate notification, the communication block from the client is relayed to a server. For this reason, on the server side, a collection result can be quickly recognized without waiting for the communication block from the client of the final circulation destination.

A plurality of clients are grouped, and communication blocks are parallel circulated in the groups. For this reason, time required for collection can be advantageously shortened.

Although the invention has been described with respect to a specific embodiment for a complete and clear disclosure, the appended claims are not to be thus limited but are to be construed as embodying all modifications and alternative constructions that may occur to one skilled in the art which fairly fall within the basic teaching herein set forth.

WHAT IS CLAIMED IS:

1. An information collection and distribution system for collecting and distributing information between a server and clients which are connected to a network,

5 wherein the server transmits communication blocks including at least addresses and pieces of distribution information of the plurality of clients to one client of the plurality of clients through said network;

each client out of said plurality of clients obtains the
10 from the communication blocks, and circulates the communication blocks in which distribution results are set to a client next in the order on the basis of the addresses;

a final client which has received the pieces of distribution information last out of said plurality of clients
15 transmits the communication block to said one client; and

said one client relays the communication block transmitted from said final client to said server.

2. The information collection and distribution system
20 according to claim 1, wherein said server recognizes a client which fails in distribution on the basis of the distribution result set in the communication block transmitted from said one client, and re-transmits the communication block to said failed client.

3. The information collection and distribution system according to claim 1, wherein each client other than said one client and said final client transmits the communication block to said one client as intermediate notification when a next
5 client as the circulation destination is in a stop state, and said one client relays the communication block transmitted from said client to said server.

4. The information collection and distribution system
10 according to claim 1, wherein said one client partitions all the other clients into a plurality of groups and transmits a communication block to one client in each of the groups;

one client in each of the groups obtains the distribution information from the communication block and circulates a
15 communication block in which a distribution result is set to the next client in the group on the basis of an address;

a final client of a circulation destination in each of the groups transmits the communication block to said one client that has partitioned the clients into groups; and

20 said one client that has partitioned the clients into groups relays the communication block transmitted from said final client of each circulation destination to said server.

5. An information collection and distribution system for collecting and distributing information between a server and clients which are connected to a network,

wherein said server transmits communication blocks
5 including at least addresses of the plurality of clients to one client of the plurality of clients through the network;
each client out of said plurality of clients sets the pieces of collection information in the communication blocks and circulates the communication blocks in which collection
10 results are set to a client next in the order on the basis of the addresses;

a final client which has received the pieces of distribution information last out of said plurality of clients transmits the communication block to said one client; and
15 said one client relays the communication block transmitted from said final client as one communication block to said server.

6. The information collection and distribution system
20 according to claim 5, wherein said server recognizes a client which fails in collection on the basis of the collection result set in the communication block transmitted from said one client, and re-transmits the communication block to said failed client.

7. The information collection and distribution system according to claim 5, wherein each client other than said one client and said final client transmits the communication block to said one client as intermediate notification when a next
5 client as the circulation destination is in a stop state, and
said one client relays the communication block transmitted from said client to said server.

8. The information collection and distribution system
10 according to claim 5, wherein said one client partitions all the other clients into a plurality of groups and transmits a communication block to one client in each of the groups;

one client in each of the groups obtains the distribution information from the communication block and circulates a
15 communication block in which a distribution result is set to the next client in the group on the basis of an address;


a final client of a circulation destination in each of the groups transmits the communication block to said one client that has partitioned the clients into groups; and

20 said one client that has partitioned the clients into groups relays the communication block transmitted from said final client of each circulation destination to said server.


ABSTRACT OF THE DISCLOSURE

A server transmits distribution communication blocks to a relay client and other clients through the Internet. The communication blocks include at least addresses and pieces of distribution information of the relay client and the other clients. The relay client obtains the pieces of distribution information from the distribution communication blocks, and circulates the communication blocks in which distribution results are set to a client next in the order on the basis of the addresses. The last client that receives the distribution communication block transmits it to the relay client. The relay client relays the distribution communication block back to the server.

FIG. 1










FIG. 4

FIG.5




FIG.6




FIG.7




FIG.8







FIG.9










FIG.12

FIG.13





FIG. 14






FIG.16





FIG.17






FIG. 18A




FIG. 18B




FIG. 18C




FIG. 18D

FIG.19




FIG. 20




FIG.22




FIG.23




FIG.24





FIG. 25



Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Declaration and Power of Attorney For Patent Application

特許出願宣言書及び委任状

Japanese Language Declaration

日本語宣言書

下記の氏名の発明者として、私は以下の通り宣誓します。

As a below named inventor, I hereby declare that:

私の住所、私書箱、国籍は下記の私の氏名の後に記載された通りです。

My residence, post office address and citizenship are as stated next to my name.

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者であると（下記の名称が複数の場合）信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

INFORMATION COLLECTION AND

DISTRIBUTION SYSTEM

上記発明の明細書（下記の欄でx印がついていない場合は、本書に添付）は、

the specification of which is attached hereto unless the following box is checked:

- 月 日に提出され、米国出願番号または特許協定条約
国際出願番号を _____ とし、
(該当する場合) _____ に訂正されました。

- ☐ was filed on _____
as United States Application Number or
PCT International Application Number
_____ and was amended on
_____ (if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、運輸規則法典第37編第1条56項に定規されると
おり、特許資格の有無について重要な情報を開示する義務が
あることを認めます。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

Japanese Language Declaration (日本語宣言書)

私は、米国法典第35編119条(a)-(d)項又は365条(b)項に基づき、米国以外の国の少なくとも一カ国を指定している特許協力条約365(a)項に基づき国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している。本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示しています。

Prior Foreign Application(s)

外国での先行出願

2000-019230

(Number)
(番号)

Japan

(Country)
(国名)

27/January/2000

(Day/Month/Year Filed)
(出願年月日)

Priority Not Claimed
優先権主張なし

☐

(Number)
(番号)

(Country)
(国名)

(Day/Month/Year Filed)
(出願年月日)

☐

私、第35編米国法典119条(a)項に基づいて下記の米国特許出願規定に記載された権利をここに主張いたします。

(Application No.)
(出願番号)

(Filing Date)
(出願日)

(Application No.)
(出願番号)

(Filing Date)
(出願日)

私は、下記の米国法典第35編120条に基づいて下記の米国特許出願に記載された権利、又は米国を指定している特許協力条約365条(c)に基づき権利をここに主張します。また、本出願の各請求範囲の内容が米国法典第35編112条第1項又は特許協力条約で規定された方法で先行する米国特許出願に開示されていない限り、その先行米国特許出願提出日以降で本出願書の日付内または特許協力条約国際提出日までとの期間中に入手された、連邦規則法典第37編1条56項で定義された特許資格の有無に関する重要な情報について開示義務があることを認識しています。

(Application No.)
(出願番号)

(Filing Date)
(出願日)

(Status: Patented, Pending, Abandoned)
(現況: 特許許可済、保属中、放棄済)

(Application No.)
(出願番号)

(Filing Date)
(出願日)

(Status: Patented, Pending, Abandoned)
(現況: 特許許可済、保属中、放棄済)

私は、私自身の知識に基づいて本宣言書中で私が行なう表明が真実であり、かつ私の入手した情報と私の信じていることに基づき表明が全て真実であると信じていること、さらに故意になされた虚偽の表明及びそれと同等の行為は米国法典第18編第1001条に基づき、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような虚偽による虚偽の声明を行なえば、出願した、又は既に許可された特許の有効性が失われることを認識し、よってここに上記のごとく宣誓を致します。

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of application.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Japanese Language Declaration

(日本語宣言書)

委任状： 私は下記の発明者として、本出願に関する一切の手續きを米特許商標局に対して遂行する弁護士または代理人として、下記の者を指名いたします。(弁護士、または代理人の氏名及び登録番号を明記のこと)

James D. Halsey, Jr., 22,729; Harry John Staas, 22,010; David M. Pitcher, 25,908; John C. Garvey, 28,607; J. Randall Beckers, 30,358; William F. Herbert, 31,024; Richard A. Gollhofer, 31,106; Mark J. Henry, 36,162; Gene M. Garner II, 34,172; Michael D. Stein, 37,240; Paul I. Kravetz, 35,230; Gerald P. Joyce, III, 37,648; Todd E. Marlette, 35,269; Harlan B. Williams, Jr., 34,756; George N. Stevens, 36,938; Michael C. Soldner, 41,455; Norman L. Ourada, 41,235; Kevin R. Sprvak, P-43,148; and William M. Schertler, 35,348 (agent)

書類送付先

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (list name and registration number)

Send Correspondence to:

STAAS & HALSEY
 700 Eleventh Street, N.W.
 Suite 500
 Washington, D.C. 20001

直接電話連絡先: (名前及び電話番号)

Direct Telephone Calls to: (name and telephone number)

STAAS & HALSEY
 (202) 434-1500

唯一または第一発明者名	Full name of sole or first inventor
発明者の署名	Inventor's signature
日付	Date
住所	Residence
国籍	Citizenship
私書箱	Post Office Address
第二共同発明者	Full name of second joint inventor, if any
第二共同発明者	Second inventor's signature
日付	Date
住所	Residence
国籍	Citizenship
私書箱	Post Office Address

Taichi UJIGAWA

Taichi Ujigawa Oct. 13, 2000

Kobe, Japan

Japanese

C/O FUJITSU KOBE
 ENGINEERING LIMITED

2-1-15 Kano-cho, Chuo-ku, Kobe-shi,
 Hyogo 650-0001 Japan

Katzumi HAYASHI

Katzumi Hayashi Oct. 13, 2000

Kobe, Japan

Japanese

C/O FUJITSU KOBE
 ENGINEERING LIMITED

2-1-15 Kano-cho, Chuo-ku, Kobe-shi,
 Hyogo 650-0001 Japan

(第三以降の共同発明者についても同様に記載し、署名をすること)

[Supply similar information and signature for third and subsequent joint inventors.]

第三共同発明者		Full name of third joint inventor, if any Masaya KIMURA
第三共同発明者	日付	Third inventor's signature Masaya Kimura Date Oct. 13, 2000
住 所		Residence Kobe, Japan
国 籍		Citizenship Japanese
私書箱		Post Office Address c/o FUJITSU KOBE ENGINEERING LIMITED 2-1-15 Kano-cho, Chuo-ku, Kobe-shi, Hyogo 650-0001 Japan
第四共同発明者		Full name of fourth joint inventor, if any Yasutaka ODA
第四共同発明者	日付	Fourth inventor's signature Yasutaka Oda Date Oct. 13, 2000
住 所		Residence Kobe, Japan
国 籍		Citizenship Japanese
私書箱		Post Office Address c/o FUJITSU KOBE ENGINEERING LIMITED 2-1-15 Kano-cho, Chuo-ku, Kobe-shi, Hyogo 650-0001 Japan

第五共同発明者		Full name of fifth joint inventor, if any
第五共同発明者	日付	Fifth inventor's signature Date
住 所		Residence
国 籍		Citizenship
私書箱		Post Office Address
第六共同発明者		Full name of sixth joint inventor, if any
第六共同発明者	日付	Sixth inventor's signature Date
住 所		Residence
国 籍		Citizenship
私書箱		Post Office Address

(第七以降の共同発明者についても同様に
記載し、署名をすること)

(Supply similar information and signature for
seventh and subsequent joint inventors.)